




Film grips


Suitable for griping thin films

Selectable from wide range according to sample material and dimension












[Special purpose model]

to beerer barbere means		
	Light weight aluminum model	
	Capacity:250N	
	(FC-21U,FC-41U,FC-21UQ)	
Single urethane grip model	FC-21U (Weight:40g) M6	
Film width: max 20mm	VIII	Suitable for thin films with the
Film thickness: max 2mm		◄····· single urethane grip minimizing
		the possible damage to the sample
Single urethane grip model	FC-41U (Weight:70g) M6	
for wide width		Wide width model of single
Film width: max 40mm		◄····· urethane grip model
Film thickness: max 2mm		
Lever operation single	FC-21UQ (Weight:50g) M6	
urethane grip model		One touch lever operation model of
Film width: max 20mm		◄····· single urethane grip model
Film thickness: max 0.2mm		
		<u> </u>
Special custom model		
Please ask us for		
measurement of special	9	
material and dimension	Contact us for the detail	

		Applications		
90 degree peel test		180 degree peel test	Film material strength test	
Seal adhesive strength	est	Seal adhesive strength test	Strength test of film material	
	degree	180 degree		
JISZ1707(1997)	General ru	iles of plastic films for food packagin	g	
JISZ0238(1998)	Testing me	Testing methods for heat sealed flexible packages		
JISZ1711(1994)	Polyethyle	Polyethylene film bags		
JISZ1712(1997)	Oriented polypropylene films for packaging			



[Dimension]



Model	Dimension W*H*D(mm)	
FC-21	20*53*8	
FC-20	20*64*12	
FC-40	40*64*12	
FC-21U	20*64.5*12	
FC-41U	40*64.5*12	
FC-21UQ	20*64.5*12	

Differences of models

[General caution]

- -The contents may be changed without notice in advance.
- -This product is designed for measurement purpose only.
- -Some samples of certain material/shape may not be used with these attachments even if it is within specification. Please contact us for the detail.
- -Do not copy and use this content without authority.